








Series **Solid Glass**



Low-noise and low-power extract axial fan suitable for use in Zone 1

- Motor type: AC
- Casing material: Plastic
- Timer: Turn off timer
- Humidity sensor

Lineup	Connected air duct size, mm	Maximum airflow, m ³ /h	Sound pressure level LpA at 3 m, dB(A)	Pull cord	Humidity sensor	Timer
 100 Solid Glass	100	85	26	✗	✗	✗
 100 Solid Glass Red	100	85	26			✗
 100 Solid Glass Black	100	85	26			✗
 100 Solid Glass L	100	85	26			✗
 100 Solid Glass L Red	100	85	26			✗
 100 Solid Glass L Black	100	85	26			✗
 100 Solid Glass T	100	85	26	✗	✗	✓

	100 Solid Glass T Red	100	85	26			✓
	100 Solid Glass T Black	100	85	26			✓
	100 Solid Glass T1	100	85	26			✓
	100 Solid Glass T1 Red	100	85	26			✓
	100 Solid Glass T1 Black	100	85	26			✓
	100 Solid Glass TH	100	85	26	✗	✓	✓
	100 Solid Glass TH Red	100	85	26		✓	✓
	100 Solid Glass TH Black	100	85	26		✓	✓
	100 Solid Glass V	100	85	26	✓		✗
	100 Solid Glass V Red	100	85	26	✓		✗
	100 Solid Glass V Red	100	85	26	✓		✗