Series **Solid Glass**



Axial fans with glass panels for extract ventilation suitable for use in Zone 1

- Casing material: Plastic
- Humidity sensor

Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m³/h	Sound pressure level LpA at 3 m, dB(A)	Pull cord	Humidity sensor	Timer	Number of speeds
100 Solid Glass	100	8	85	26	✕	✕	✕	1
100 Solid Glass Red	100	8	85	26	✕	✕	✕	1
100 Solid Glass Black	100	8	85	26	✕	✕	✕	1
100 Solid Glass L	100	8	85	26	✕	✕	✕	1
100 Solid Glass L Red	100	8	85	26	✕	✕	✕	1
100 Solid Glass L Black	100	8	85	26	✕	✕	✕	1

 100 Solid Glass T	100	8	85	26	✗	✗	Turn off timer	1
 100 Solid Glass T Red	100	8	85	26	✗	✗	Turn off timer	1
 100 Solid Glass T Black	100	8	85	26	✗	✗	Turn off timer	1
 100 Solid Glass T1	100	8	85	26	✗	✗	Turn off timer, Turn on timer	1
 100 Solid Glass T1 Red	100	8	85	26	✗	✗	Turn off timer, Turn on timer	1
 100 Solid Glass T1 Black	100	8	85	26	✗	✗	Turn off timer, Turn on timer	1
 100 Solid Glass TH	100	8	85	26	✗	✓	Turn off timer	1
 100 Solid Glass TH Red	100	8	85	26	✗	✓	Turn off timer	1
 100 Solid Glass TH Black	100	8	85	26	✗	✓	Turn off timer	1
 100 Solid Glass V	100	8	85	26	✓	✗	✗	1
 100 Solid Glass V Red	100	8	85	26	✓	✗	✗	1
 100 Solid Glass V Red	100	8	85	26	✓	✗	✗	1