Series TT Silent-M EC

Mixed-flow inline fans in sound-insulated casing with EC-motors

- Sound-insulated casing
- Impeller type: Mixed-flow
- Casing material: Coated steel



Lineup	Connected air duct size, mm	Phases	Rated power, W	Maximum airflow, m³/h	Temperature sensor
TT Silent-M 100 EC	100	1	17	260	✕
TT Silent-M 125 EC	125	1	18	370	✕
TT Silent-M 150 EC	150	1	55	600	✕
TT Silent-M 160 EC	160	1	55	600	✕
TT Silent-M 200 EC	200	1	120	1240	✕
TT Silent-M 250 EC	250	1	169	1285	✕
TT Silent-M 315 EC	315	1	232	1810	✕

 TT Silent-M 100 EC R1	100	1	17	260	✗
 TT Silent-M 100 EC P	100	1	17	260	✗
 TT Silent-M 100 EC U	100	1	17	260	✓
 TT Silent-M 100 EC Un	100	1	17	260	✓
 TT Silent-M 125 EC R1	125	1	18	370	✗
 TT Silent-M 125 EC P	125	1	18	370	✗
 TT Silent-M 125 EC U	125	1	18	370	✓
 TT Silent-M 125 EC Un	125	1	18	370	✓
 TT Silent-M 150 EC R1	150	1	55	600	✗
 TT Silent-M 150 EC P	150	1	55	600	✗
 TT Silent-M 150 EC U	150	1	55	600	✓
 TT Silent-M 150 EC Un	150	1	55	600	✓
 TT Silent-M 160 EC R1	160	1	55	600	✗
 TT Silent-M 160 EC P	160	1	55	600	✗

 TT Silent-M 160 EC U	160	1	55	600	✔
 TT Silent-M 160 EC Un	160	1	55	600	✔
 TT Silent-M 200 EC R1	200	1	120	1240	✖
 TT Silent-M 200 EC P	200	1	120	1240	✖
 TT Silent-M 200 EC U	200	1	120	1240	✔
 TT Silent-M 200 EC Un	200	1	120	1240	✔
 TT Silent-M 250 EC R1	250	1	169	1285	✖
 TT Silent-M 250 EC P	250	1	169	1285	✖
 TT Silent-M 250 EC U	250	1	169	1285	✔
 TT Silent-M 250 EC Un	250	1	169	1285	✔
 TT Silent-M 315 EC R1	315	1	232	1810	✖
 TT Silent-M 315 EC P	315	1	232	1810	✖
 TT Silent-M 315 EC U	315	1	232	1810	✔
 TT Silent-M 315 EC Un	315	1	232	1810	✔