






















Series VK

















Centrifugal inline fans in plastic casings

- Motor type: AC
- Impeller type: Centrifugal impeller with backward curved blades
- Casing material: Plastic
- Control: Built-in speed controller

Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m ³ /h	Cable with mains plug	Temperature sensor
 VK 100	100	62	250	✗	✗
 VK 100 R1	100	62	250	✓	✗
 VK 100 P	100	62	250	✓	✗
 VK 100 U	100	62	250	✓	✓
 VK 100 Un	100	62	250	✓	✓
 VK 125	125	63	340	✗	✗
 VK 125 R1	125	63	340	✓	✗

	VK 125 P	125	63	340	✓	✗
	VK 125 U	125	63	340	✓	✓
	VK 125 Un	125	63	340	✓	✓
	VK 150	150	65	460	✗	✗
	VK 150 R1	150	65	460	✓	✗
	VK 150 P	150	65	460	✓	✗
	VK 150 U	150	65	460	✓	✓
	VK 150 Un	150	65	460	✓	✓
	VK 200	200	107	780	✗	✗
	VK 200 R1	200	107	780	✓	✗
	VK 200 P	200	107	780	✓	✗
	VK 200 U	200	107	780	✓	✓
	VK 200 Un	200	107	780	✓	✓
	VK 250	250	171	1100	✗	✗

 VK 250 R1	250	171	1100	✓	✗
 VK 250 P	250	171	1100	✓	✗
 VK 250 U	250	171	1100	✓	✓
 VK 250 Un	250	171	1100	✓	✓
 VK 315	315	169	1240	✗	✗
 VK 315 R1	315	169	1240	✓	✗
 VK 315 P	315	169	1240	✓	✗
 VK 315 U	315	169	1240	✓	✓
 VK 315 Un	315	169	1240	✓	✓
 VKS 200	200	166	1065	✗	✗
 VKS 200 R1	200	166	1065	✓	✗
 VKS 200 P	200	166	1065	✓	✗
 VKS 200 U	200	166	1065	✓	✓
 VKS 200 Un	200	166	1065	✓	✓