








Series **VNV KP2**








Centrifugal fan in fireproof casing

- Control: Wired control panel
- Casing material: Plastic
- Humidity sensor: Built-in
- Timer: Built-in
- Motion sensor

Lineup	Connected air duct size, mm	Maximum airflow, m ³ /h	Sound pressure level LpA at 3 m, dB(A)
 VNV-1A 80 KP2	80	63	36
 VNV-1E 80 KP2	80	100	38
 VNV-1A 80 KP2 H	80	63	36
 VNV-1A 80 KP2 I	80	63	36
 VNV-1A 80 KP2 T	80	63	36
 VNV-1A 80 KP2 TR	80	63	36
 VNV-1A 80 KP2-D	80	63	36

 VNV-1A 80 KP2-D H	80	63	36
 VNV-1A 80 KP2-D I	80	63	36
 VNV-1A 80 KP2-D T	80	63	36
 VNV-1A 80 KP2-D TR	80	63	36
 VNV-1A 80 KP2-L	80	63	36
 VNV-1A 80 KP2-L H	80	63	36
 VNV-1A 80 KP2-L I	80	63	36
 VNV-1A 80 KP2-L T	80	63	36
 VNV-1A 80 KP2-L TR	80	63	36
 VNV-1A 80 KP2-P	80	63	36
 VNV-1A 80 KP2-P H	80	63	36
 VNV-1A 80 KP2-P I	80	63	36
 VNV-1A 80 KP2-P T	80	63	36
 VNV-1A 80 KP2-P TR	80	63	36

 VNV-1E 80 KP2 H	80	100	38
 VNV-1E 80 KP2 I	80	100	38
 VNV-1E 80 KP2 T	80	100	38
 VNV-1E 80 KP2 TR	80	100	38
 VNV-1E 80 KP2-D	80	100	38
 VNV-1E 80 KP2-D H	80	100	38
 VNV-1E 80 KP2-D I	80	100	38
 VNV-1E 80 KP2-D T	80	100	38
 VNV-1E 80 KP2-D TR	80	100	38
 VNV-1E 80 KP2-L	80	100	38
 VNV-1E 80 KP2-L H	80	100	38
 VNV-1E 80 KP2-L I	80	100	38
 VNV-1E 80 KP2-L T	80	100	38
 VNV-1E 80 KP2-L TR	80	100	38

 VNV-1E 80 KP2-P	80	100	38
 VNV-1E 80 KP2-P H	80	100	38
 VNV-1E 80 KP2-P I	80	100	38
 VNV-1E 80 KP2-P T	80	100	38
 VNV-1E 80 KP2-P TR	80	100	38