

















Series **VPA**



Supply units in the compact sound- and heat-insulated casing with electric heater

- Filter: G4
- Sound insulation
- Motor type: AC
- Reheater: Electric
- Control: Remote Control
- Casing material: Galvanized steel

Lineup	Connected air duct size, mm	Speed	Maximum supply voltage, V	Rated power, W	Maximum airflow, m ³ /h	Sound pressure level LpA at 3 m, dB(A)
 VPA 100-1,8-1 LCD	100	1	230	73	190	27
 VPA 125-2,4-1 LCD	125	1	230	75	285	28
 VPA 150-2,4-1 LCD	150	1	230	98	425	29
 VPA 150-3,4-1 LCD	150	1	230	98	425	29
 VPA 150-5,1-3 LCD	150	1	400	98	425	29
 VPA 150-6,0-3 LCD	150	1	400	98	425	29

 VPA 200-3,4-1 LCD	200	1	400	193	810	30
 VPA 200-5,1-3 LCD	200	1	400	193	810	30
 VPA 200-6,0-3 LCD	200	1	400	193	810	30
 VPA 250-3,6-3 LCD	250	1	400	194	990	30
 VPA 250-6,0-3 LCD	250	1	400	194	990	30
 VPA 250-9,0-3 LCD	250	1	400	194	990	30
 VPA 315-6,0-3 LCD	315	1	400	171	1190	30
 VPA 315-9,0-3 LCD	315	1	400	171	1190	30
 VPA-1 315-6,0-3 LCD	315	1	400	296	1250	30
 VPA-1 315-9,0-3 LCD	315	1	400	296	1250	30