











Series VUT PBE EC



Suspended commercial air handling units with a counterflow polystyrene heat exchanger

- Heat exchanger type: Cross flow
- Sound insulation
- Motor type: EC
- Bypass: Auto
- Reheater: Electric
- Preheater: Optional
- BMS protocol: ModBus
- Control: Smartphone
- Casing material: Galvanized steel
- Humidity sensor: Optional

Lineup	Connected air duct size, mm	Speed	Phases	Maximum supply voltage, V	Power of electrical reheater, W	Heat recovery efficiency, max, %	Heat exchanger material	Extract filter	Supply filter	Service side	Control system	Reheater	Preheater	BMS protocol
 VUT 300 PBE EC R A21 DTV	160	1	1	230	1500	90	Polystyrene	G4	G4 (F7 option)	Right	A21	Electric	Optional	ModBus
 VUT 550 PBE EC R A21 DTV	200	1	1	230	2000	90	Polystyrene	G4	G4 (F7 option)	Right	A21	Electric	Optional	ModBus
 VUT 900 PBE EC R A21 DTV	250	1	1	230	3300	88	Polystyrene	G4	G4 (F7 option)	Right	A21	Electric	Optional	ModBus
 VUT 2000 PBE EC A21 DTV	315	1	3	400	15000	67	Aluminum	G4	G4	Right	A21	Electric	✗	ModBus
 VUT 3000 PBE EC A21 DTV	400	1	3	400	21000	72	Aluminum	G4	G4	Right	A21	Electric	✗	ModBus
 VUT 300 PBE EC L A21 DTV	160	1	1	230	1500	90	Polystyrene	G4	G4 (F7 option)	Left	A21	Electric	Optional	ModBus
 VUT 550 PBE EC L A21 DTV	200	1	1	230	2000	90	Polystyrene	G4	G4 (F7 option)	Left	A21	Electric	Optional	ModBus
 VUT 900 PBE EC L A21 DTV	250	1	1	230	3300	88	Polystyrene	G4	G4 (F7 option)	Left	A21	Electric	Optional	ModBus
 VUT 2000 PBE EC A21	315	1	3	400	15000	67	Aluminum	G4	G4	Right	A21	Electric	✗	ModBus

 VUT 3000 PBE EC A21	400	1	3	400	21000	72	Aluminum	G4	G4	Right	A21	Electric	×	ModBus
---	-----	---	---	-----	-------	----	----------	----	----	-------	-----	----------	---	--------