







## Series **VUT PBW EC**



Suspended commercial air handling units with a counterflow polystyrene heat exchanger

- Heat exchanger type: Cross flow
- Sound insulation
- Motor type: EC
- Bypass: Auto
- Reheater: Water
- Preheater: Optional
- BMS protocol: ModBus
- Control: Smartphone
- Casing material: Galvanized steel
- Humidity sensor: Optional

Lineup	Connected air duct size, mm	Speed	Phases	Maximum supply voltage, V	Heat recovery efficiency, max, %	Heat exchanger material	Extract filter	Supply filter	Service side	Control system	Reheater	Preheater	BMS protocol
 VUT 550 PBW EC R A21 DTV	200	1	1	230	90	Polystyrene	G4	G4 (F7 option)	Right	A21	Water	Optional	ModBus
 VUT 550 PBW EC L A21 DTV	200	1	1	230	90	Polystyrene	G4	G4 (F7 option)	Left	A21	Water	Optional	ModBus
 VUT 900 PBW EC R A21 DTV	250	1	1	230	88	Polystyrene	G4	G4 (F7 option)	Right	A21	Water	Optional	ModBus
 VUT 900 PBW EC L A21 DTV	250	1	1	230	88	Polystyrene	G4	G4 (F7 option)	Left	A21	Water	Optional	ModBus
 VUT 2000 PBW EC A21 DTV	315	1	1	230	67	Aluminum	G4	G4	Right	A21	Water	✘	ModBus
 VUT 3000 PBW EC A21 DTV	400	1	3	400	72	Aluminum	G4	G4	Right	A21	Water	✘	ModBus