













Серия **ВКФ**





Осевые вентиляторы низкого давления в стальном корпусе для настенного монтажа

- Тип двигателя: АС
- Тип крыльчатки: Осевой

Модельный ряд	Размер подключаемого воздуховода, мм	Номинальная мощность, Вт	Максимальный расход воздуха, м ³ /час
 ВКФ 2Д 250	250	80	1060
 ВКФ 2Д 300	300	145	2310
 ВКФ 4Д 250	250	60	850
 ВКФ 4Д 300	300	75	1310
 ВКФ 4Д 350	350	140	2350
 ВКФ 4Д 400	400	180	3740
 ВКФ 4Д 450	450	250	5280

 ВКФ 4Д 500	500	450	6570
 ВКФ 4Д 550	550	750	9700
 ВКФ 4Д 630	630	800	12200
 ВКФ 2Е 200	200	55	860
 ВКФ 2Е 250	250	80	1050
 ВКФ 2Е 300	300	145	2230
 ВКФ 4Е 250	250	50	800
 ВКФ 4Е 300	300	75	1340
 ВКФ 4Е 350	350	140	2500
 ВКФ 4Е 400	400	180	3580
 ВКФ 4Е 450	450	250	4680
 ВКФ 4Е 500	500	420	7060
 ВКФ 4Е 550	550	550	8800
 ВКФ 4Е 630	630	750	11900

 ВКФ 6Д 710	710	1150	15440
 ВКФ 6Д 800	800	1850	25000