MV 100 V ASA Series	 Application Decoration of supply and exhaust vents of public, residential and industrial ventilation systems. Used for correct air flow distribution in premises.
	 Wall or ceiling mounting. Design Made of quality and durable plastic.
	 Multi-element structure. The internal part is fixed to the base with latches for easy cleaning without dismantling. Screw fixing.
	The grille has slanted vanes.
	Colour modifications
Modifications	white brown beige
MV 100 V ASA – model with a round flange (V)	



- Fitted with a round connecting flange for mounting with Ø 100 mm air duct.
- Suitable for direct mounting with VENTS VKO 100 fan.
- MV 100 Vs ASA model with a round flange and a protecting insect screen.



MV 100 VU ASA – model with a multi-section flange (VU)



- Equipped with a multi-section connecting flange for mounting with Ø100, 125 mm or 55x110 mm air duct.
- MV 100 VUs ASA model with a multi-section flange and a protecting insect screen.



Overall dimensions

Model	Dimensions [mm]						
	⊡B	⊡H	L	L1	Flange (D)	Air pass, [m ²]	Fig. no.
MV 100 V ASA	154	110	15	45	100	0.004	1, 2
MV 100 VU ASA	154	110	15	39	100, 125, 55x110	0.0067	1, 3
B		<	D		<u>ah</u>		HD
Fig.	. 1			Fig. 2		Fig. 3	